



Standard Thru-hole Ceramic Filter for FM Receiver - LT10.7M Series

FEATURES

- RoHS Compliant (Pb-Free)
- Low Insertion Loss and Wide/Narrow Band-width Types Available
- Industry de factor Standard Leads Spacing
- Superior Shock/Vibration Performance and Environmental Characteristics

STANDARD SPECIFICATIONS

Part Series	3dB Band Width (kHz)	20dB Band Width (kHz) Max	Insertion Loss (dB) Max	Spurious Attenuation (9-12MHz)(dB) Min	Input/Output Impedance (Ohms)	Notes
LT10.7MA5	280±50	650	6	30	330	
LT10.7MS2	230±50	600	6	40	330	
LT10.7MS3	180±40	520	7	40	330	
LT10.7MJ	150±40	400	10	38	330	
LT10.7MA5A10	280±50	590	2.5±2.0	30	330	Low-Loss
LT10.7MS2A10	230±50	520	3.0±2.0	35	330	Low-Loss
LT10.7MS3A10	180±40	470	.5±1.5	35	330	Low-Loss
LT10.7MJA10	150±40	360	4.5±2.0	35	330	Low-Loss
LT10.7MA19	350 Min	950	3±2	20	470	Wide BW
LT10.7MA20	330±50	680	4±2	30	330	Wide BW
LT10.7MHY	110±30	350	7±2	30	330	Narrow BW
LT10.7MFP	20 Min	95	6.0 Max	24	600	Narrow BW

OUTLINE DRAWING

